



◆拡管形

RoHS2指令対応品

規格	呼び ビニル	規格	呼び ナイロン	各部の寸法							標準色	適合電線範囲 撚線mm ² AWG		適合工具	一箱入数
	BVF0.08-3		—	3.2	5.2	3.2	5.9	9.0	12.5	17.5	黄※	0.08	28	DS05N DH-1B	1,000 (100×10)
	BVF0.08-V3.5		—	3.7	5.7	3.2	7.7	9.0	15.0	20.0					
UL	BVF0.3-2		—	2.2	5.2	3.2	5.9	9.0	12.5	17.5	黄※	0.1 ∩ 0.3	26-22	*DS05N *DH-1B *DS-A5	1,000 (100×10)
UL	BVF0.3-3		—	3.2											
	BVF0.3-V3.5		—				7.7								
	BVF0.3-L3.5		—				6.7		15.0	20.2					
UL	BVF0.3-3.5		—			3.7		9.0			黄※				
UL	BVF0.3-4		—		6.6		7.7								
UL	BVF0.5-2		—	2.2	5.2	3.2	5.9	9.0	12.5	17.5	黄※	0.3 ∩ 0.5	22-20	*DS05N *DH-1B *DS-A5	1,000 (100×10)
UL	BVF0.5-3		—	3.2			7.7								
	BVF0.5-V3.5		—				6.7		15.0	20.0					
	BVF0.5-L3.5		—		5.7										
UL	BVF0.5-3.5		—		6.6	3.7		9.0			黄※				
UL	BVF0.5-4		—				7.7								
UL	BVF0.5-5		—	5.3	8.0		7.0								
UL	BVF1.25-M3	Ⓢ	BPF1.25-M3	3.2	5.6	4.1 (4.0)	5.0	9.0	14.2	18.7	赤※	0.5 ∩ 1.65	20-16	*DS-Hi3 *DS-Hi34S *DH-1B *DS-A5	500 (100×5)
UL	BVF1.25-3	Ⓢ	BPF1.25-3		6.0		4.4								
	BVF1.25-V3		BPF1.25-V3		5.7		6.3		15.2	19.7					
UL	BVF1.25-L3	Ⓢ	BPF1.25-L3		5.9		6.5		15.6	20.1					
UL	BVF1.25-C3.5		BPF1.25-C3.5	3.7	6.0		4.5		12.8	17.3					
UL	BVF1.25-S3.5		BPF1.25-S3.5		5.7		6.3		13.5	18.0					
UL	BVF1.25-3.5	Ⓢ	BPF1.25-3.5		6.0		4.4		14.2	18.7					
UL	BVF1.25-V3.5		BPF1.25-V3.5		5.7		6.3		15.2	19.7					
UL	BVF1.25-L3.5	Ⓢ	BPF1.25-L3.5	4.3	5.9		6.5		15.6	20.1					
UL	BVF1.25-A3.5	Ⓢ	BPF1.25-A3.5		6.4		6.8		15.4	19.9					
UL	BVF1.25-S4	Ⓢ	BPF1.25-S4				6.8		15.6	20.1					
UL	BVF1.25-4	Ⓢ	BPF1.25-4		7.0		6.5		16.2	20.7					
UL	BVF1.25-A4	Ⓢ	BPF1.25-A4	5.3	8.3		7.1		16.8	21.3					
UL	BVF1.25-5	Ⓢ	BPF1.25-5				7.0		17.0	21.5					
UL	BVF1.25-6	Ⓢ	BPF1.25-6		6.4		7.6								
UL	BVF2-3	Ⓢ	BPF2-3	3.2	5.5	4.7 (4.5)	4.4	9.0	14.2	18.7	青※	1.04 ∩ 2.63	16-14	*DS-Hi4 *DS-Hi34S *DH-1B *DS-A5	500 (100×5)
	BVF2-A3		BPF2-A3		5.7		6.1								
UL	BVF2-S3.5	Ⓢ	BPF2-S3.5	3.7	6.5		6.5		15.7	20.2					
UL	BVF2-3.5	Ⓢ	BPF2-3.5		6.5		6.0		15.8	20.3					
UL	BVF2-M4	Ⓢ	BPF2-M4	4.3	6.4		6.7		15.6	20.1					
UL	BVF2-S4	Ⓢ	BPF2-S4		6.6		8.0		15.8	20.3					
UL	BVF2-4	Ⓢ	BPF2-4		6.9		7.2		16.2	20.7					
UL	BVF2-A4	Ⓢ	BPF2-A4		8.3										
UL	BVF2-5	Ⓢ	BPF2-5	5.3	8.5		8.5		17.2	21.7					
UL	BVF2-6	Ⓢ	BPF2-6		6.4		9.5		20.2	24.7					
UL	BVF3.5-4		—	4.3	8.0	6.0	7.5	13.5	17.8	26.0	黄※	2.63 ∩ 4.6	12		300 (100×3)
UL	BVF3.5-5		—	5.3											
UL	BVF5.5-M4		—	4.3	7.1	6.4	7.9	13.5	19.5	26.7	黄※	2.63 ∩ 6.64	12-10	*DS-Hi5 *DH-1B *DS-A5	300 (100×3)
UL	BVF5.5-4		—		8.5		7.2		18.0	25.2					
UL	BVF5.5-5		—		9.0		8.5		19.0	26.2					
UL	BVF5.5-6		—		12.5				23.5	30.7					
UL	BVF5.5-8		—	8.4	15.0		10.5		24.5	31.7					200 (100×2)

1. 各呼びの印は、UL登録品、CSA登録品です。

2. CSA登録品としてご使用の際は、注文時にご指示ください。カートンがCSA品用となります。

3. 上記寸法表にかぎらず特注品もご相談ください。() はBPF形の寸法です。

4. *印はUL適合工具です。

※…表の絶縁被覆のカラーは、あくまで標準色です。ご用意できるカラーはP. 20を参照下さい。