



RoHS2指令対応品

規格			曲げ	呼び	各部の寸法								適合電線範囲			適合工具	一箱入数		
					φd ₂	B	L	F	E	φD	φd ₁	T	単線mm	撚線mm ²	AWG				
			●	R0.08-3	3.3	5.2	12.5	5.9	4.0	2.3	0.45	0.8	—	0.08	28	DS031 DH-1B	1,000 (100×10)		
			●	R0.08-M3.5	3.7	5.5	14.5	7.7											
	UL		●	R0.3-2	2.2	5.2	12.5	5.9	4.0	2.3	0.8	0.65	0.32 ∩ 0.6	0.1 ∩ 0.3	26-24	*DS031 *DH-1B *DS-A5	1,000 (100×10)		
	UL		●	R0.3-3	3.2														
	UL		●	R0.3-3.5	3.7	6.6	15.0	7.7											
	UL		●	R0.3-4	4.3														
	UL	SE	●	R0.5-2	2.2	5.2	12.5	5.9	4.0	2.3	1.2	0.5	0.5 ∩ 0.8	0.2 ∩ 0.5	24-20	*DS031 *DH-1B *DS-A5	1,000 (100×10)		
	UL	SE	●	R0.5-3	3.2														
	UL	SE	●	R0.5-3.5	3.7	6.6	15.0	7.7											
	UL	SE	●	R0.5-4	4.3														
	UL	SE	●	R0.5-5	5.3	8.0		7.0											
	UL	SE	●	R1.25-2	2.5	5.5	12.0	4.8	4.5	3.4	1.7	0.8	0.57 ∩ 1.44	0.25 ∩ 1.65	22-16	*DS031 *DS-H18 *DH-1B *DS-A5 *DS-Hi34S PALM-125A PALM-12A	1,000 (100×10)		
UL	SE	●	R1.25-3																
	UL	SE	●	R1.25-M3														13.8	6.6
			R1.25-N3	3.2	5.6													14.9	7.6
	UL	SE	●	R1.25-V3		6.6	14.4	6.6											
	UL	SE	●	R1.25-L3		8.0	15.5	7.5											
	UL	SE	●	R1.25-S3.5		5.5	12.0	4.8											
	UL	SE	●	R1.25-M3.5		5.5	13.8	6.6											
	UL	SE	●	R1.25-N3.5	3.7	5.6	14.9	7.6											
UL	SE	●	R1.25-3.5		6.6	14.4	6.6												
UL	SE	●	R1.25-S4	4.3															
UL	SE	●	R1.25-4		8.0	15.5	7.5												
UL	SE	●	R1.25-5	5.3															
	UL	●	R1.25-L5			18.5													
	UL	SE	●	R1.25-6	6.4	11.5	20.2	10.0											
	UL	SE	●	R1.25-8	8.4														
	UL	SE	●	R1.25-10		13.6	21.8	10.5											
			●	R1.25-A10	10.5	22.0	29.5	14.0											
			●	R1.25-12	13.0														
	UL	SE	●	R2-3		6.6	13.0	5.2	4.5	4.2	2.3	0.8	1.14 ∩ 1.82	1.04 ∩ 2.63	16-14	*DS-H18 *DS-H214 *DH-1B *DS-A5 *DS-E14 *DS-Hi34S PALM-125A PALM-12A	1,000 (100×10)		
	UL	SE	●	R2-M3	3.2	5.5	12.4												
	UL	SE	●	R2-L3			13.7	6.5											
	UL	SE	●	R2-M3.5		5.8	13.9												
UL	SE	●	R2-3.5	3.7		13.0	5.2												
	UL	SE	●	R2-L3.5		6.6	16.0	8.3											
	UL	SE	●	R2-M4			14.3	6.5											
	UL	SE	●	R2-S4	4.3		16.0	8.3											
UL	SE	●	R2-4		8.5	16.5	7.8												
UL	SE	●	R2-S5	5.3	9.5	17.0													
UL	SE	●	R2-5																
UL	SE	●	R2-L5																
UL	SE	●	R2-6	6.4	12.0	21.5	11.0												
UL	SE	●	R2-8																
	UL	●	R2-A8	8.4	18.0	27.5	14.0												
	UL	●	R2-B8		16.0	28.5	16.0												
	UL	SE	●	R2-10		14.5	24.0	12.3											
	UL	●	R2-A10	10.5	18.0	27.5	14.0												
	UL	●	R2-B10		20.0	32.5	18.0												
	UL	SE	●	R2-12		17.0	26.9	13.9											
	UL	●	R2-A12	13.0	22.0	29.5	14.0												
	UL	●	R3.5-S4	4.3	7.0	17.1	8.3	5.3	5.0	3.0	1.0	1.82 ∩ 2.4	2.63 ∩ 4.6	12	*DS-H18 *DS-H214 *DH-1B *DS-A5 *DS-E14 PALM-125A	1,000 (100×10)			
	UL	SE	●	R3.5-4		8.5											17.8		
	UL	SE	●	R3.5-5	5.3														
	UL	SE	●	R3.5-6	6.4	12.0	21.8										10.5		
	UL	SE	●	R3.5-8	8.4	14.5	25.0										12.5		
	UL	SE	●	R3.5-10	10.5														
	UL	●	R3.5-12	13.0	20.0	31.0	15.7												

1. 各呼びの印は、JIS規格品、UL登録品、CSA登録品です。

2. CSA登録品としてご使用の際は、注文時にご指示ください。カートンがCSA品用となります。

3. 上記寸法表にかぎらず特注品もご相談ください。

4. *印はUL適合工具です。5. ●・▲印は舌部曲げ加工対象品です。

(注) 曲げ加工品は各規格に適合していません。曲げ加工品の各寸法は曲げる角度により、異なります。