



RoHS 2指令対応品

規格				曲げ	呼　　び	各　部　の　寸　法							適　合　電　線　範　囲			適合工具	一箱入数				
						φ d ₂	B	L	F	E	φ D	φ d ₁	T	単線mm	撚線mm ²			AWG			
	UL	CS	●	R 80-6	6.4	27.0	53.0	20.5	19.0	19.5	14.5	2.3	9.27	76.28	3/0	*DS-H0150 *12号A *DS-E150 *DS-E200M *DS-E250M REC-Li325	25				
	UL	CS	●	R 80-8	8.4																
	UL	CS	●	R 80-10	10.5																
	UL	CS	●	R 80-12	13.0																
	UL	CS	●	R 80-L8	8.4	32.0	67.0	32.0													
	UL	CS	●	R 80-L10	10.5																
	UL	CS	●	R 80-L12	13.0																
	UL	CS	●	R 80-14	15.0																
	UL	CS	●	R 80-16	17.0																
			●	R 80-18	19.0																
	UL	CS	●	R 80-20	21.0																
	UL	CS	●	R 80-24	25.0																
			●	R 100-6	6.4	28.5	54.0	20.8					19.0	22.3	16.4	2.6	10.41	96.3	4/0	*DS-H0150 *12号A *DS-E150 *DS-E200M *DS-E250M REC-Li325	20
	UL	CS	●	R 100-8	8.4																
JIS	UL	CS		R 100-10	10.5																
JIS	UL	CS		R 100-12	13.0																
	UL	CS	●	R 100-L8	8.4	32.0	68.0	33.0													
	UL	CS	●	R 100-L10	10.5																
	UL	CS	●	R 100-L12	13.0																
JIS	UL	CS		R 100-14	15.0																
JIS	UL	CS		R 100-16	17.0																
JIS				R 100-18	19.0																
JIS	UL	CS		R 100-20	21.0																
	UL	CS	●	R 100-24	25.0																
	UL	CS	●	R 150-8	8.4	36.0	66.0	21.0	27.0	26.5	19.5	3.2					11.68	117.2	250-300 MCM	*DS-H0150 *12号A *DS-E150 *DS-E200M *DS-E250M REC-Li325	15
JIS	UL	CS		R 150-10	10.5																
JIS	UL	CS		R 150-12	13.0																
	UL	CS		R 150-S14	15.0																
	UL	CS		R 150-S16	17.0																
	UL	CS	●	R 150-L8	8.4		82.0	37.0													
	UL	CS	●	R 150-L10	10.5																
	UL	CS	●	R 150-L12	13.0																
JIS	UL	CS		R 150-14	15.0																
JIS	UL	CS		R 150-16	17.0																
JIS				R 150-18	19.0																
JIS	UL	CS		R 150-20	21.0																
	UL	CS	●	R 150-24	25.0																
	UL	CS	●	R 150-27	28.0																

1. 各呼びの印は、JIS規格品、UL登録品、CSA登録品です。
2. CSA登録品としてご使用の際は、注文時にご指示ください。カートンがCSA品用となります。
3. 上記寸法表にかぎらず特注品もご相談ください。
4. *印はUL適合工具です。5. ●・▲印は舌部曲げ加工対象品です。

(注) 曲げ加工品は各規格に適合していません。曲げ加工品の各寸法は曲げる角度により、異なります。